

ToooAir

Dual band
PTToC with UHF
Commercial and
80 Channel CB

PTToC 4G IP
Radio with
UHF

39 Pre-
Programmable
UHF Channels
(402MHz-480MHz)

80 Channel
UHF CB

78
Programmable
RX only
Channels

GPS Receiver
In-Built

Numeric
Keypad

USB &
Desktop
Charging

Signal
Strength and
Battery Level
Indicator

The TA-680 is the handheld Australia has been waiting for, unique in its feature offering. Now users can communicate back to the office anywhere in Australia on their own private fleet network and also talk locally to open networks on UHF channels or CB all from one portable.

With inbuilt GPS the unit can be tracked, displayed and managed using the ToooAir dispatch platform. TA-680's powerful features are enhanced by a numeric keypad, colour TFT display, easy switching between modes, SOS emergency call and USB charging.

The unit is a fully featured PTToC (Push to Talk over Cellular) Two Way radio with integrated analog UHF capability offering 39 pre-programmable commercial channels and 80 Channel CB. A further 78 channels are user programmable receive only frequencies that can be added to the scan group.



TA-680

PTToC Network Features

Group Call (One to Many)

User can select a pre-programmed group and instigate a group call and talk to all members of the group. The radio can be a part of multiple groups and choose the group it belongs to

Individual Private Call (One to One)

User can select an individual radio or the dispatcher and perform a one on one private call outside the group

Internal GPS Engine

The internal GPS engine reports its position every 60 seconds to the dispatcher (Programmable). GPS acquisition status is shown on the radio LCD display

Text Message

The dispatch operator can send instant text messages to the radio, all the text messages are recorded on the dispatcher

Radio Stun

The dispatch software can stun a radio, should the radio be stolen or abused. Radio stun can also be controlled by the system platform, if the fleet is not using a dispatcher

SOS Emergency Call

SOS emergency broadcast to dispatch platform and all fleet users

Twin Antenna

Maximum performance is achieved across the wide band of 400MHz, 1800MHz & 2100MHz utilizing twin antenna design

UHF Features

UHF Commercial

39 UHF dealer programmable frequencies from 400 to 480MHz with CTCSS and DCS, BCL, Hi/Lo Power, Roger Beep, Frequency + Channel display, ToT and Scan

UHF CB (477Mhz)

80 Channel with CTCSS/DCS, Hi/Lo Power, Direct channel access via keypad, Duplex and Scan